

Specification Sheet

Part Number: 596-00249



Solar Marker, Reflective, Non-Adhesive, CAUTION: SOLAR CIRCUIT, 4" x 2", VL, Red, 25/pkg

Article Number

596-00249

Type

CSCSNAP4R

Color

Red (RD)

Features & Benefits

- Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.
- Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.
- Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.
- The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.

Quantity Per

pack

Product Description

These HellermannTyton photovoltaic caution and power source markers are designed to meet the requirements of the National Electrical Code (NEC) International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Coiled markers are pre-printed, non-adhesive and made of a UV stable vinyl. Markers can be opened and snapped over cables for long-term, reflective, permanent identification. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed. Vinyl markers fit all standard PV cables or electrical metallic tubing (EMT) conduits.

Short Description

Solar Marker, Reflective, Non-Adhesive, CAUTION: SOLAR CIRCUIT, 4" x 2", VL, Red, 25/pkg

Global Part Name

CSCSNAP4R-V-RD

Technical Description

Pre-Printed Solar Marker, Reflective, Non-adhesive, Coiled, "CAUTION: SOLAR CIRCUIT", 4" X 2", Red

Length L (Imperial)

2.0

Length L (Metric)

50.80

Width W (Imperial)

4.0

Width W (Metric)

101.6

Material

Vinyl

Material Shortcut

V

Halogen free

Yes

Operating Temperature (Metric)

-18°F to +200°F (-29°C to +93°C)

ROHS Complaint

Yes

Certification/Specification WEB

IFC 2012 NEC2011

Package Quantity(Imperial)

25

Package Quantity (Metric)

25

Customs Number

3919905060