

Product marked with ESD protective symbol to identify used for ESD control

"Fabric upholstered chairs accomplish this by using conductive fibers woven into the fabric. The fabric is then connected through the components of the chair, through the cylinder, base and casters (or drag chain) to the floor." [ESD Handbook TR20.20 Seating section 5.3.5.2 Types and Selection

Description:

Desco's 07200 Statshield® Dissipative Chair Cover can convert a regular chair into an ESD protective chair when grounded. The drag chain must connect the chair back and seat covers and make reliable contact with ESD flooring to remove electrostatic charges to ground. Using the same fabric as ESD smocks, the cover's conductive fibers attenuate electrostatic fields shielding ESD sensitive items. It's one size fits standard sized chairs and covers both seat and chair backs. In addition to shielding, the Statshield Chair Cover is low charging antistatic, and dissipative.

Specifications:

Grounding resistance: 1 megohm hermetically sealed resistor

24" long chain with current limiting resistor in series Chain Length:

Fabric Weight: 5 oz per square yard

Fabric Content: 80% polyester, 19% cotton, and 1% BASF carbon suffused mono-filament nylon

Fabric Color: Roval Blue

Carbon Mono-filament: Conductive at 10E4 ohms, non-flaking and

non-slouahina

Surface Resistance of Fabric: 10E6 - 10E8 ohms tested per ESD TR53 Seating test

based on ANSI/ESD STM12.1, Seating - Resistive

Measurement

Static Decay Rate: 5000 volts to 500 volts in less than 0.01

seconds, per FTMS-101C

Size

Seat: 18" x 20", maximum diameter 19" nominal

Back: 15 1/2" x 18 1/2", maximum diameter 17" nominal

Laundering Instructions:

If need be, this cover can be laundered. Use cool or warm water. Maximum temperature 120 °F. Do not use bleach, tumble dry on cool.

Installation Instructions:

Attach top part of cover to chair back and bottom part of cover (with grounding chain attached) to chair seat. Make sure cover is fitted, centered, and secured to chair. Secure the ground chain to center post underneath chair with hook and loop and make sure ground chain makes contact with grounded ESD floor. Suggest a chain minimum length of 6 inches making contact along the floor.

If not otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice





Statshield® Dissipative Chair Cover



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER 07200

DATE May 2011