

## Cable gland - G-INS-M12-S68N-PNES-GY - 1411123

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide 6, External cable diameter 3 mm ... 6.5 mm, Shielding: No, Connecting thread: M12



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	4.0 g
Custom tariff number	39269097
Country of origin	Turkey

### Technical data

#### Dimensions

Length	32 mm
Wrench size, union nut	15 mm
Wrench size, support	15 mm
Hexagon angular dimension GRP	17.1 mm
Length of the connecting thread	8 mm
Feed-through hole diameter	12.1 mm ... 12.2 mm
External cable diameter	3 mm ... 6.5 mm

#### Ambient conditions

Degree of protection	IP68 (5 bar / 0.5 h)
Ambient temperature (operation)	-20 °C ... 100 °C (static)

#### General

No. of conductors	1
Cable gland material	Polyamide 6
Seal material	Neoprene

# Cable gland - G-INS-M12-S68N-PNES-GY - 1411123

## Technical data

### General

Cable seal material	Neoprene
Shielded	No
Thread type on connection side	M12
Torque	2 Nm (Union nut)
Flammability rating according to UL 94	V2
Color	silver-grey RAL 7001

### Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

## Classifications

### eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

### ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

## Approvals

### Approvals

---

#### Approvals

CSA / UL Recognized / VDE Zeichengenehmigung / cUL Recognized / cULus Recognized

---

#### Ex Approvals

---




#### Approvals submitted

---

## Approval details

# Cable gland - G-INS-M12-S68N-PNES-GY - 1411123

## Approvals



## Drawings

Dimensional drawing

