



#### General ordering data

Order No.	0376860000
Part designation	ASK 1/15
Version	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 15
EAN	4008190141202
Qty.	100 pc(s).

#### Product notes

Note, technical data	Note: max. conductor size = 2.5 mm <sup>2</sup> when using the cross-connection. Twin wire-end ferrules ZH 0.5 - ZH 1.5 can be used.
Note, accessories	Contact Sleeve order no. 0553300000; AP ASK 1 order no. 0380360000.

#### Additional technical data

Colour of insulating material	beige
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 15
Insulating material	PA 66
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V2
Version	Fuse terminal

#### CSA rating data

Voltage (CSA)	300 V
CSA current	6.3 A
Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 12

**Conductors for clamping (additional connection)**

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	4 mm <sup>2</sup>

**Conductors for clamping (rated connection)**

Clamping range, min.	0.13 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	9 mm
Clamping screw	M 3
Blade size	0.6 x 3.5 mm
Tightening torque range	0.5...1.0 Nm
Torque level with DMS electric screwdriver	2
Gauge to IEC 60947-1	A3
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	4 mm <sup>2</sup>
Stranded, min.	1.5 mm <sup>2</sup>
Stranded, max.	4 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	4 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	4 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	1.5 mm <sup>2</sup>
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 12
AWG conductor size, min.	0.13 mm <sup>2</sup>
AWG conductor size, max.	3.31 mm <sup>2</sup>

**Dimensions**

Width	8 mm
Height of lowest version	34 mm
Length	58 mm
TS 15 offset	26 mm

**Disconnect terminals**

Torque level with DMS electric screwdriver	2
--	---

**Display element**

Operating voltage for display, max.	500 V
Type of voltage for indicator	AC/DC

**Fuse terminals**

Cartridge fuse	G-Si. 5 x 20
----------------	--------------

#### Fuse terminals

Display	Without LED
Fuse holder (cartridge holder)	Pivoting
Operating voltage, max.	400 V
Type of voltage for indicator	AC/DC

#### Rating data

Rated cross-section	4 mm <sup>2</sup>
Rated voltage	500 V
Rated impulse voltage	6 kV
Rated current	6.3 A
Current with max. conductor	6.3 A
Pollution severity	3

#### UL rating data

Voltage (UL)	300 V
Current (UL)	10 A
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

#### Approvals

Approvals institutes



#### Classifications

ETIM 2.0	EC000899
ETIM 3.0	EC000899
eClass 4.1	27-14-11-16
eClass 5.0	27-14-11-16
eClass 5.1	27-14-11-16

#### Similar products

Order No.	Part designation	Version
-----------	------------------	---------